



WD306-99

MAVIG



Article No.: **WD306/2.0/800/99F** Mobile X-Ray Protective Shield, Pb 2.00 mm, Width 80.0 cm

Made in France



WD306-99 – Mobile X-Ray Protective Shield

Working in radiation exposed environment requires appropriate protection. Therefore this mobile shield combines upper and lower body protection.

The modular mobile shield WD306-99 consists of an upper section with transparent lead glass and a lower shield part. MAVIG offers the mobile shield WD306-99 with a lead equivalent value of Pb 2.00 mm. Electro-conductive casters and sturdy side handles allow for easy and safe positioning.

- **MAVIG lead glass with excellent light transmission**
- **Leight weight alumium frame construction**
- **Lead equivalent** Pb 2.00 mm
- **Overall height** 187.0 cm
- **Dimension of window** approx. 70.0 cm x 80.0 cm (W x H)
- **Side handles for secure movement**
- **Electro-conductive casters/wheels**

MAVIG GmbH
X-Ray Protection and
Medical Suspension Systems

Stahlgruberring 5
81829 Munich
Germany

PO Box 82 03 62
81803 Munich
Germany

Phone +49 (0) 89 / 420 96 - 0
Fax +49 (0) 89 / 420 96 - 200
e-Mail info@mavig.com



WD308-99



Article No.:	WD308/1.0/800/99F	Mobile X-Ray Protective Shield, Pb 1.00 mm, Width 80.0 cm
	WD308/1.0/1300/99F	Mobile X-Ray Protective Shield, Pb 1.00 mm, Width 130.0 cm
	WD308/2.0/1300/99F	Mobile X-Ray Protective Shield, Pb 2.00 mm, Width 130.0 cm

Made in France



WD308-99 – Mobile X-Ray Protective Shield

Working in radiation exposed environment requires appropriate protection. Therefore this mobile shield combines upper and lower body protection.

The WD308-99 with its wide lead glass area in two different available widths provides maximum protection and an unimpeded view for personal. MAVIG offers the mobile shield WD308-99 also in two different lead equivalent values depending on your needs. Electro-conductive casters and sturdy side handles allow for easy and safe positioning.

- **MAVIG lead glass with excellent light transmission**
- **Leight weight alumium frame construction**
- **Lead equivalents** Pb 1.00 mm and Pb 2.00 mm available
- **Overall height** 185.0 cm
- **Glass part dimensions** 70.0 or 120.0 cm x 175.0 cm (W x H)
- **Side handles for secure movement**
- **Electro-conductive casters/wheels**

MAVIG GmbH
X-Ray Protection and
Medical Suspension Systems

Stahlgruberring 5
81829 Munich
Germany

PO Box 82 03 62
81803 Munich
Germany

Phone +49 (0) 89 / 420 96 - 0
Fax +49 (0) 89 / 420 96 - 200
e-Mail info@mavig.com