



Management
System
EN ISO
13485:2016
www.tuv.com
ID: 0000075020

Skiff MRI

ANTIMAGNETIC TROLLEY

Directive
93/42/EEC | **CE**



■ SAFE PATIENT TRANSFER UP TO 3 TESLA IN YOUR MRI UNIT ■

Entirely made out of plastics and aluminium

Antimagnetic
IV pole



Steering
handles



Independent
brakes

Antimagnetic wheels, (non-ferrous rolling). The stretcher is highly manoeuvrable in 3 Telsa field.



ERGONOMIC

PU cover mattress for extra comfort



PATIENT COMFORT

Removable velcro-free mattress, protective casing and lying surface for easy cleaning and enhanced infection control.



HYGIENE

Variable height, steering handles and independent brakes for easy manoeuvrability.



HANDLING

Specifications

Overall width: 740 mm
Overall length: 2100 mm

Adjustable height: 500 to 850 mm
Lying width: 620 mm
Lying length: 1900 mm

Backrest: 0° to 90°

Wheels: 125mm with independent brakes

Mattress thickness: 80 mm

Maximum load: 165 kg



Foldable barriers

STANDARD FEATURES

- Aluminium frame
- 4 wheels (2 with independent brake)
- PU mattress
- Backrest on racks
- 1 antimagnetic IV Pole
- Anti-shocks bumpers
- 2 IV pole holders
- 2 foldable barriers
- 2 fixed steering handles
- Adjustable height side pedal

Adjustable backrest up to 90°



Antimagnetic wheels

